

32" Lite Professional LED Monitor

HYU-CC-MM32002



Key Features

- HD: 3840*2160, 4 times higher than normal monitor
- Turn on the screen to automatically detect the resolution of the input signal in the upper right corner of the screen
- Clear: delicate and realistic, conveying true colors, showing the true colors
- Bright: The quality is improved, only for better presentation
- Adopt industrial screen, high brightness, high contrast
- High-precision standard regulated power supply, specially designed for industrial equipment, supporting 24 hours × 365 days of uninterrupted work
- It adopts full metal casing, strong structure, fireproof, moisture proof and shockproof, especially suitable for equipment that is susceptible to electromagnetic interference
- Adopt 10bit image chip processing technology, high pixel progressive scan, fine texture
- Support intelligent 3D noise reduction, eliminate afterimage function, dynamic brightness, contrast color optimization technology
- Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality
- LED has small volume, low energy consumption, zero radiation, stable image, no impact on the eyes, natural health
- 5 ms extremely fast response, avoiding the tailing phenomenon of images in high speed operation
- Using nanotechnology, the picture is more three-dimensional, transparent
- This machine also comes with a splicing function, no external splicer

Specifications

Model	HYU-CC-MM32002
Display	
Product Type	Professional Monitor
Screen Size	32"
Screen Type	LED
Screen Ratio	16:9
Brightness	500nit
Contrast Ratio	3000:1
Response Time	5ms
Visual Area	694x376 mm
Display Color	16.7M
Viewing Angle	Horizontal 160°, Vertical 170°
Clearness	3840*2160 (Compatible with 4k)
Control method	Panel infrared
Interface	
Input port	HDMI*3/VGA*1/Rf*1/PC Audio in*1/CVBS*1/USB*2
Output port	Coax out*1/Earphone*1
Audio	
Audio Output	2*Stereo speakers
General	
Power Supply	110-220V
Power frequency	50-60Hz
Total Power	50W
Case	professional fireproof iron case, plastic frame (plastic stand)
Dimensions	730*430*74 does not include foot height (foot height 45mm)
Packing Size	765*110*500
Installation method	Base, wall mount
Product Weight	5.1kg
Gross Weight	5.5kg
Working environment temperature	20°C is the most suitable
Working environment humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Packing size (4pcs in 1 case)	790*500*500mm
Gross Weight	24kg

Dimensions

