

Bluetooth Touch Keypad HYU-AC-SAH3EMM001

Key Features



Bluetooth



Add/Delete Users



Opening Record

- Waterproof, conforms to IP66
- Metal housing, anti-vandal
- Card type: 125KHz EM Card & 13.56MHz Mifare Card
- iOS and Android available
- Add / Delete users by APP
- Support checking Opening Record
- Support Gateway
- Multiple Access Modes: Smartphone, Fingerprint, Card, PIN



Specifications

| Model | HYU-AC-SAH3EMM001 |
|--|--|
| User Capacity Common User Visitor User Panic User | Hardware User: 1000 APP User: 100 (including 255 fingerprint / card/ PIN users) 988 10 2 |
| Pin Length | 4 ~ 6 digits |
| Operating Voltage Idle Current Active Current | 12 ~ 18V DC ≤ 60mA ≤ 150mA |
| Proximity Card Reader Radio Technology Read Range | EM & Mifare 125KHz & 13.56MHz 2 ~ 6cm |
| Wiring Connections | Relay output, exit button, alarm, door contact, Wiegand input / output |
| Relay Adjustable Relay Output Time Lock Output Load | One (NO, NC, Common) 0~99 Seconds (5 seconds default) 2 Amp Maximum |
| Wiegand Interface PIN Output | EM card: Wiegand 26 ~ 44 bits input & output (Factory default: Wiegand 26bits) Mifare card: Wiegand 26~44 bits,56bits,58bits input & output (Factory default: Wiegand 34bits) 4 bits,8bits (ASCII),10 digits Virtual Number(Factory default:4bits) |

| | |
|---|---|
| Environment Operating Temperature Operating Humidity | Meets IP66 -40°C ~ 60°C (-40°F ~ 140°F) 0%RH ~ 98%RH |
| Physical Color Dimensions Unit Weight Shipping Weight | Zinc-Alloy Sliver & Black L148 x W43.5 x H22 (mm) 330g 405g |

Dimensions

