

26-Port Full Gigabit Managed Ethernet switch HYU-NE-SW-M24FM001



Key Features


- 22-Port 10/100/1000Base-T + 2 Combo + 2 (100/1000M) SFP
- L2+ features provide better manageability, security, QoS, and performance.
- Support L2+ Switching features including 802.1Q VLAN, Mirroring, Port isolation, IGMP Snooping, DHCP Snooping, LLDP, Ethernet+ management, IP Source Guard, ARP inspection, ACLs etc.
- Support spanning tree STP (802.1D) and RSTP (802.1W).
- Jumbo frames support up to 9.6K kilobytes.
- Support enhanced management through WEB, CLI, TELNET, SSH, SNMP.
- Support cable diagnosis.
- G.8032, support <50ms industrial quick ring protection.

Specification

Model	HYU-NE-SW-M24FM001
Performance (Switching capacity and forwarding rate)	
Capacity in Millions of Packets per Second (mpps) (64-byte packets)	38.69M
Switching Capacity in Gigabits per Second (Gbps)	256G
Interface	
Ports	22-Port 10/100/1000Base-T + 2x Combo ports + 2x (100/1000M) SFP slots
Layer 2 Switching	
Spanning Tree Protocol (STP)	Standard Spanning Tree 802.1d Rapid Spanning Tree (RSTP) 802.1w
G.8032 ERPS	<50ms ring protection for industrial high reliable application
Aggregation	Link Aggregation Control Protocol (LACP) IEEE 802.3ad; Up to 13 groups; Up to 16 ports per group
VLAN	Support up to 4K VLANs simultaneously (out of 4096 VLAN IDs); Port-based VLAN; 802.1Q tag-based VLAN
IGMP v1/v2 snooping	IGMP limits bandwidth-intensive multicast traffic to only the requesters; supports 1024 multicast groups (source-specific multicasting is not supported)
Security	
Secure Shell (SSH) Protocol	SSH secures Telnet traffic in or out the switch, SSH v1 and v2 are supported
Secure Sockets Layer (SSL), HTTPS	SSL encrypts the http traffic, allowing advance secure access to the browser-based management GUI in the switch
Port Security	Locks MAC Addresses to ports, and limits the number of learned MAC addresses
DHCP Snooping	Prevent unauthorized configuration and use of IP addresses, while providing support for IP Source Guard and ARP detection
IP Source Guard	Prevents datagram with spoofed addresses from being in the network
ARP Inspection	Prevent ARP spoofing attacks and ARP
Storm control	Prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on a port
ACLs	Support for up to 256 entries; Drop or rate limitation based on source and destination MAC, VLAN ID or IP address, protocol, port, differentiated services code point (DSCP) / IP precedence, TCP/ UDP source and destination ports, 802.1p priority, Ethernet type, Internet Control Message Protocol (ICMP) packets, IGMP packets, TCP flag
Quality of Service	
Hardware Priority Queue	Support 8 hardware queues
Scheduling	8 COS queues per port support strict priority and weighted round-robin (WRR)
Classification	Port based; 802.1p(PCP) VLAN priority based
Rate Limiting	Ingress policer; egress shaping and rate control; per VLAN, per port and flow based
Management	
Web GUI interface	Built-in switch configuration utility for browser-based device configuration (HTTP/ HTTPS). Supports configuration, system dashboard, maintenance, and monitoring
Dual Image	Dual image provides independent primary and secondary OS files for backup while upgrading
Firmware upgrade	Web browser upgrade (HTTP/ HTTPS) and TFTP; Upgrade through console port as well

Port mirroring	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe. Up to N-1 (N is Switch's Ports) ports can be mirrored to single destination port. A single session is supported
Other management	Single IP management; HTTP/HTTPS; SSH; RADIUS; DHCP Client; SNMP; cable diagnostics; ping; syslog; Telnet client (SSH secure support)
Green Ethernet	
Green and Energy-saving Ethernet (EEE)	Compliant IEEE802.3az Energy Efficient Ethernet Task Force. Automatically turns off power on Gigabit Ethernet RJ-45 port when detecting link down or Idle of client. Active mode is resumed without loss of any packets when the switch detects the link up
Cable length detection	Adjusts the signal strength based on the cable length. Reduces the power consumption for cables shorter
General	
Jumbo frames	Frame sizes up to 9KB supported on Gigabit interfaces
MAC Table	Up to 8K MAC addresses.
Discovery	
Link Layer Discovery Protocol (LLDP)	Used by network devices for advertising their identities, capabilities, and neighbors on a IEEE 802 local area network, principally wired Ethernet.
Minimum Requirements	
<p>Web browser: Mozilla Firefox version 2.5 or later, Microsoft Internet Explorer version 6 or later;</p> <p>Category 5 Ethernet network cable;</p> <p>TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in network</p>	
Environmental (preliminary)	
Dimensions	440 x 290 x 44.5mm / 4.1kg
Working Environment	Operating temperature: -20 to 55 °C; Storage temperature: -20°C to 75 °C; Operating humidity: 10% to 90%, relative, non-condensing

Dimensions



- | | |
|---------------------------|--|
| A. PWR/ RUN LED indicator | D. CONSOLE Port |
| B. 22*Gigabit RJ45 Ports | E. 2*Sets of Gigabit TP/SFP Combo Port |
| C. 2*Gigabit SFP Ports | F. 100-240VAC, 50/60Hz |

Application

