

5MP Lite 4IN1 5X AF HD Dome IR 30m HYU-CC-CHDV24001



Key Features

- 1/2. 8" SONY Starvis Back-illuminated CMOS sensor
- CVI/AHD/TVI/CVBS 4 IN 1
- IR Distance Max. 30m
- IP66 Outdoor, OSD&UTC Support

Specifications

| Model | HYU-CC-CHDV24001 |
|-----------------------|--|
| Video Output Mode | AHD: 8M@15fps, 5M@20fps/12.5fps, 4MP@30fps/25fps/15fps; 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps |
| Camera | |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS sensor |
| Image Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | AUTO |
| Scanning System | Progressive Scan |
| Lens | |
| Focus Length | 2.7-13.5mm |
| Focus Control | Auto |
| Lens Type | Motorized |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 42μ x 4PCS |
| Infrared Distance | 30M |
| IR Status | AGC Auto Control |
| Camera Features | |
| Starlight | / |
| Day/Night | YES |
| OSD Menu | YES |
| WDR | YES |
| UTC | YES |
| Noise Reduction | 3DNR |
| White Balance | AUTO/MANUAL |
| Gain Control | AUTO |
| General | |
| Housing | Metal, IP66 |
| Bracket | NO |
| Operation Temperature | -10°C ~ +50°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 750mA |
| Dimension | Φ 142 x 142(H) mm |
| Weight | 1200g |