

24" Professional LED Monitor

HYU-CC-MM24002



Key Features

- HD: 1920*1080 with higher definition than the normal monitor
- Turn on the screen to automatically detect the resolution of the input signal in the lower left corner of the screen
- Clear: delicate and realistic, conveying true colors, showing the true colors
- Bright: The quality is improved, only for better presentation
- Adopt industrial screen, high brightness, high contrast
- High-precision standard regulated power supply, specially designed for industrial equipment, supporting 24 hours × 365 days of uninterrupted work
- Adopt 10bit image chip processing technology, high pixel progressive scan, fine texture
- Support intelligent 3D noise reduction, eliminate afterimage function, dynamic brightness, contrast color optimization technology
- Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality
- LED has small volume, low energy consumption, zero radiation, stable image, no impact on the eyes, natural health
- 5 ms extremely fast response, avoiding the tailing phenomenon of images in high speed operation
- Using nanotechnology, the picture is more three-dimensional, transparent

Specifications

Model	HYU-CC-MM24002
Display	
Product Type	Professional Monitor
Screen Size	24"
Screen Size	LED
Screen Ratio	16:9
Brightness	300nit
Contrast Ratio	1000:1
Response Time	5ms
Viewing Area	521.28×293.22 mm
Display Color	16.7M
Viewing Angle	Horizontal 160°, Vertical 170°
Clearness	1920*1080 (Compatible with 4k)
Control method	Panel
Refresh Rate	60Hz
Interface	
Input port	HDMI, VGA, RCA, audio input
Audio	
Audio Output	withstereo speaker
Head set hole	Audio Input
General	
Power Supply	12V / 4A
Total Power	36W
Casing	Fireproof plastic
Dimensions	556mm*334.5mm, not including the foot height (foot height: 76mm)
Packing Size	615mm*105mm*455mm
Installation method	Base, wall mount
Product Weight	3.2kg
Gross Weight	4.2kg
Working environment temperature	20°C is the most suitable
Working environment humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Packing size (5pcs in 1 case)	643mm*550mm*494mm
Gross Weight	22kg

Dimensions

