

UTP Category 5E Cables HYU-CAB-UC5

Model		HYU-CAB-UC5	
Product specification	HSYV-5e 4 × 2 × 0.45		
Test Standard	ISO/IEC11801, TIA-568-C.2, IEC61156-6		
Conductor	Material	Solid-Bare Copper	
	AWG	25	
	Nom.O.D.(mm)	0.45±0.005 mm	
	DC resistance	≤115 Ω/km	
Insulation	Material	HDPE	
	Thickness	0.17±0.01 mm	
	Diameter	0.81±0.05 mm	
	Color	Blue/White- Blue Orange /White-Orange	Green/White-Green Brown/White-Brown
Pitch	Offset pitch	≤25 mm	
	Cable pitch	≤140 mm	
Sheath	Material	PVC (complies RoHS/REACH)	
	External O.D.	4.7±0.3 mm	
	Color	Gray (RAL7046)	
	Tensile strength	>13.5 Mpa	
	Thickness	0.55±0.05 mm	
Surface Printing	Letter height	3.0±0.3 mm	
	Color	Black	
	Print error & Space	1±0.005 m	
	Case number	Yes	
Packing	Packing	Carton	
	Once packing dimension	340mm*220mm*340mm	
	Twice packing dimension	360mm*470mm*360mm	
	Twice packing quantity	2 cases	
Packing length	305±1 m		
Ripcord	Yes		
Ambient temperature	-20°C ~ 60°C		

