

Network Video Recorder

HYU-CC-RN3432001



Key Features

- Support Ultra 265/H.265/H.264 video formats
- 32-channel input
- Third-party IP cameras supported with ONVIF conformance (Profile S, Profile G, Profile T)
- Support 2-ch HDMI, 1-ch VGA, HDMI2 at up to 4K (3840 x 2160) resolution
- HDMI1/VGA and HDMI2 independent outputs provided
- Up to 12MP resolution recording
- 4 SATA HDDs, up to 8TB for each HDD
- Various fisheye de-warping modes for live view and playback for both web interface and GUI
- ANR technology to enhance the storage reliability when the network is disconnected
- Support cloud upgrade

Specifications

Model	HYU-CC-RN3432001
Video/Audio Input	
IP Video Input	32-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI1/VGA: 1920 x 1080p/60Hz, 1920 x 1080p/50Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz HDMI2: 4K (3840 x 2160) /60Hz, 4K (3840 x 2160)/ 30Hz, 1920 x 1080p /60Hz, 1920 x 1080p / 50Hz, 1600 x 1200
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	32-ch
Audio Output	1-ch, RCA
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
Decoding	
Decoding format	Ultra 265/H.265/H.264
Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30, 32 x 960p@25
Hard Disk	
SATA	4 SATA interface
Capacity	up to 8TB for each HDD
Smart	
VCA Detection by Camera	Face detection, Intrusion detection, Cross line detection, Audio Detection, Defocus detection, Scene change detection, Audio tracking
VCA Search	Face search, Behaviour Search
Statistical Analysis	People counting
External Interface	
Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0
Alarm In	16-ch
Alarm Out	4-ch
General	
Power Supply	12V DC Power Consumption: ≤12 W (without HDD)
Dimensions (W × D × H)	440mm × 344mm × 44mm (17.3" × 13.5" × 1.7")
Weight (without HDD)	≤ 3.14 Kg (6.92 lb)
Working Environment	-10°C ~ +55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)

Dimensions

