

Door controller with POE HYU-AC-NCARC200002



Specifications

Model	HYU-AC-NCARC200002
Maximum Readers	Up to 2 Readers (Wiegand and/or RS-485)
Maximum Doors	2
Maximum Users	50.000
Ethernet	Yes, 10/100 Mbps
RS-485	Yes
SSL Enabled	Yes
Bluetooth	Yes (BLE-10m)
Wi-Fi	Yes
PoE+	Yes, IEEE 802.3 af/at
Reader Power Output	Max. 12V DC @ 0.250A
Reader Types	2 Reader Port for any Wiegand or Matrix Reader
Interface	RS-485 (For Matrix Reader Only) and Wiegand IN
Exit Switch Port	Yes
Door Status Sense	Programmable NO, NC
Door Lock Relay	Maximum 30 V DC @ 2A, Relay SPDT, Form C
Door Lock Power	12V DC @ 0.5A
AUX-IN Port	Yes
AUX-Out Port	30V DC @ 2A, Relay SPDT, Form C
LED	Yes (Tri Color)
Input Power	PoE+ (IEEE 802.3 af),12VDC @ 1.8A OR 12 VDC @ 2A Power Adaptor
CPU	ARM Processor, 800MHz
Memory	256MB Flash, 256MB RAM
Mounting	Wall Mount OR Din-Rail Mounting Options
Dimensions (W x H x D)	140 x 78 x 25mm
Weight (kg)	0.45 (0.99 lbs.)
Humidity	5% to 95% RH Non-Condensing
Operating Temperature	-10°C to + 50°C (32°F to 122°F)