

### UTP Category 6 Cables

### HYU-CAB-UC6LSZH

Model		HYU-CAB-UC6LSZH		
Product specification	HSYV-6 4×2×0.52			
Test Standard	ISO/IEC11801, TIA-568-C.2, YD/T1019			
Conductor	Material	Solid-Bare Copper		
	AWG	24		
	Nom.O.D.(mm)	0.52±0.03 mm		
	DC resistance	≤95 Ω/km		
Insulation	Material	HDPE		
	Thickness	0.2±0.02 mm		
	Diameter	0.93±0.05 mm		
	Color	Blue/White- Blue	Green/White-Green	
		Orange /White-Orange	Brown/White-Brown	
Pitch	Offset pitch	≤20 mm		
	Cable pitch	≤120 mm		
Sheath	Material	PVC (complies RoHS/REACH)		
	External O.D.	5.8±0.3 mm		
	Color	Orange		
	Tensile strength	>13.5 Mpa		
	Thickness	0.6±0.05 mm		
Surface Printing	Letter height	3.0±0.3 mm		
	Color	Black		
	Print error & Space	1±0.005 m		
	Case number	Yes		
Packing	Packing	Carton		
	Once packing dimension	420mm*205mm*420mm		
	Twice packing dimension	450mm*440mm*445mm		
	Twice packing quantity	2 cases		
Packing length	305±1 m			
Ripcord	Yes	Crossing backbone	Yes	
Ambient temperature	-20°C ~ 60°C			

