

Face and Card Standalone Access Control HYU-AC-SAV1EM001

Key Features



- Metal housing, anti-vandal
- Standalone with offline Time Attendance
- 1000 face users, 3000 card users (including 10 administrators)
- Card type: EM Card or Mifare Card (Optional)
- Multiple Access: face or card, card + face, face only or card only
- With Wiegand 26 or 34 bits input & output
- With 200000 log capacity



Specifications

| Model | HYU-AC-SAV1EM001 |
|-----------------------|---|
| User Capacity | 3,000 |
| Face | 1,000 |
| Card | 3,000 |
| Log Capacity | 200,000 |
| Operating Voltage | 12V DC |
| Idle Current | ≤140mA |
| Active Current | ≤230mA |
| Display | 2.4 TFT Color Screen LCD |
| Camera | Dual HD cameras |
| Infrared Light | Dual IR |
| Identification Speed | <0.6s |
| Identification Way | Face / Card, Card + Face, Face, Card |
| Face FAR | <0.001% |
| Face FRR | <1% |
| Proximity Card Reader | EM or Mifare |
| Radio Technology | 125KHz 13.56MHz |
| Read Range | 1cm |
| Wiring Connections | Relay Output, Exit Button, DOTL, Alarm, Wiegand Input, Wiegand Output |
| Wiegand Interface | Wiegand 26 or 34 bits Input & Output (default: 26bits) |

| | |
|--|--|
| Environment Operating Temperature Operating Humidity | Indoor -20°C ~ 50°C (-4°F ~ 122°F) 20%RH-80%RH |
| Physical Surface Finish Dimensions Unit Weight Shipping Weight | Zinc-Ally Enclosure Power Coat L145 × W68 × D25 (mm) 450g 550g |

Dimensions

