HYUNDAI

Network Cabinet HYU-NE-NCS42001

Main material

All is made of high-quality SPCC Cold Rolled Steel Thickness: Frame: 1.5mm Square-hole post: 1.5-2.0mm Side door: 1.0mm Shelf board: 1.2mm Tempered glass: 4.0mm



Features

• Easy installation and maintenance

The removable mesh front and single and double curved opened rear doors mean the cabinet is easy to install and maintain. The single or double leaf side door options can also be opened independently.

• High Stability

The cabinet can be fitted with castor wheels and supporting feet if required. The maximum static holding of the rack is 1000kgs.

• Surface Finish

The cabinet includes a powder coating surface finish which ensures it remains grease and corrosion free. The surface finish complies with relevant ROHS requirements.


• Multiple Choice

Different heights can be chosen based the capacity of equipment, and mounting base is optional, to reach the requirements of fixed cabinet, bottom line, cold wind below the bottom, dust rodent.

• Appearance

Elegant design, exquisite workmanship, precise dimensions, this product can be placed in the engine room and the office, make your office space looks modern and contemporary.

Structure Diagram Product Standard Configuration



Model	HYU-NE-NCS42001								
S/N	Specification	Qty	Material	Surface Finish	Remark				
1	Rear door	1			See front & rear door type				
2	Side panel	2	SPCC t1.0	Powder coated	Small round lock				
3	19" rails	4	SPCC t2.0	Powder Coated					
4	Mounting angle	4/6	SPCC t1.2	Powder Coated	6pcs for over 33U				
5	Top cover	1	SPCC t1.2	Powder Coated					
6	Frame	2	SPCC t1.5	Powder Coated					
7	Cable management slot	2	SPCC t1.0	Powder Coated	Only used for 800 width cabinet				
8	Front door	1			See front & rear door type				
9	Mounting spacer	8/12	SPCC t1.2	Powder Coated	Only used for 800 width cabinet: 6pcs for over 33U				
10	Bottom	1	SPCC t1.2	Powder Coated					
11	Cable entry panel	4	SPCC t1.2	Powder Coated					
12	2" heavy duty castor	4							
Hardware kits with cabinet									
А	M12 adjustable feet	4	Steel	Nickel-plated	Height: 100MM				
В	M6 screw& nuts	20/40	Steel	Nickel-plated	40pcs for over 33U				
С	Trox tooling	1	Steel						

Specification

Madal	Capacity (U)	Size (mm)			CKD
Model		Width	Depth	Height	Packing parts
HYU-NE-NCS42001	42	600	800	2000	3

Front & Rear door type



Front & rear door

- Tempered glass door.
- Small lock / Long-handled lock
- Reversible right or left handed doors.
- Turning angle is over 180 degrees.
- Material: Sheet steel and 4MM safety glass
- Surface Finish: Powder coated