

Bluetooth Touch Key Access Controller HYU-AC-SAHF3EMM001

Key Features



Bluetooth



Add/Delete Users



Opening Record

- Capacitive Fingerprint Sensor, touch keypad
- Waterproof, conforms to IP66
- Metal housing, anti-vandal
- Card type: 125KHz EM Card & 13.56MHz Mifare Card
- iOS and Android available
- Add / Delete users by APP
- Support checking Opening Record
- Support Gateway
- Multiple Access Modes: Smartphone, Fingerprint, Card, PIN



Specifications

Model	HYU-AC-SAHF3EMM001
User Capacity Common User Visitor User Panic User	Hardware User: 1000 APP User: 100 (including 255 fingerprint / card/ PIN users) 988 (100 Fingerprint Users + 888 PIN/Card Users) 10 2
Pin Length	4 ~ 6 digits
Operating Voltage Idle Current Active Current	12 ~ 18V DC ≤ 60mA ≤ 150mA
Proximity Card Reader Radio Technology Read Range	EM & Mifare 125KHz & 13.56MHz 2 ~ 6cm
Wiring Connections	Relay output, exit button, alarm, door contact, Wiedand input / output
Relay Adjustable Relay Output Time Lock Output Load	One (NO, NC, Common) 0~99 Seconds (5 seconds default) 2 Amp Maximum

Wiegand Interface	EM card: Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits)
PIN Output	Mifare card: Wiegand 26~44 bits,56bits,58bits input & output (Factory default: Wiegand 34bits) 4 bits,8bits (ASCII),10 digits Virtual Number(Factory default:4bits)
Environment	Meets IP66
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Operating Humidity	0%RH ~ 98%RH
Physical	Zinc-Alloy
Color	Sliver & Black
Dimensions	L148 x W43.5 x H22 (mm)
Unit Weight	330g
Shipping Weight	405g

Dimensions

