

# 6-port Full Gigabit E Network Managed Industrial PoE Switch HYU-NE-SW-MI4PF001



## Key Features

- Gigabit access, SFP fiber port uplink
  - Support non-blocking wire speed forwarding
  - Support full duplex based on IEEE802.3x and half duplex based on Backpressure
  - Support Gigabit Ethernet port and Gigabit SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios
- Intelligent PoE power supply
  - IEEE802.3af/at PoE standard, without damaging non PoE devices
  - PoE network management, realize PoE port power allocation, priority setting, port power status viewing, time scheduling, etc
  - 4\*10/100/1000Base T RJ45 ports can support POE power supply to meet the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios
- Extreme optimization, minimalist application
  - Real time fault alarm and fault location
  - Remote upgrade, remote restart, and factory reset.
  - Local platform, cloud platform and mobile APP operation and maintenance management
  - Visualized network topology management, VLAN division, QoS, link aggregation, ring network management, port mirroring, port control and bandwidth management
  - According to the application requirements of the industry, we have abandoned the complicated network management configuration while retaining the practical network management functions. Through the operation and maintenance platform, network deployment and centralized operation and maintenance can be quickly realized
- Stable and reliable
  - CCC, CE, FCC, RoHS.
  - Low power consumption, No fan design, aluminum shell.
  - The user friendly panel can show the device status through the LED indicator of PWR, SYS, Link, L/A

### Specification

Model	HYU-NE-SW-MI4PF001
<b>Interface Characteristics</b>	
Fixed Port	4 *10/100/1000Base T PoE ports Data/Power 2*100/1000Base X uplink SFP ports (Data) 2 groups of V+, V redundant DC power port (5P phoenix terminal)
Ethernet Port	Port 1-4 support 10/100/1000Base T auto sensing, full/half duplex MDI/MDI X self-adaption
Twisted Pair Transmission	10BASE T: Cat3,4,5 UTP (≤100 meter) 100BASE TX: Cat5 or later UTP (≤100 meter) 1000BASE T: Cat5e or later UTP (≤100 meter)
SFP Slot Port	Gigabit SFP optical fiber interface, default no included optical modules (optional order single mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable/ Distance	Multi-mode: 850nm/ 0 ~ 500M, S ingle mode: 1310nm/0 ~ 40KM, 1550nm / 0 ~ 120KM.
<b>Chip Parameter</b>	
Network Management Type	Simple web network management, loud platform management
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3x
Forwarding Mode	Store and Forward (Full wire speed)
Switching Capacity	12 Gbps
Forwarding Rate@64byte	8.93 Mpps
MAC	2K
Buffer Memory	2M
Jumbo Frame	9.2K
LED Indicator	Power/System: SYS (Green), Network: Link (Yellow), PoE: PoE (Green), Fiber port: L/A (Green)
Reset Switch	Press and hold for 6 seconds and release to restore the factory default settings Short press 2 times (1 second interval) to switch to the unmanaged state
<b>PoE &amp; Power Supply</b>	
PoE Port	Port 1 to 4 IEEE802.3af/at
PoE Management	POE port output on/off View real time power status of POE port
Power Supply Pin	Default: 1/2 (+) 3/6 (-)
Max Power Per Port	30W IEEE802.3af/at
Total power/Input Voltage	60W/48VDC
Power Consumption	Standby: <6W Full load: <60W
Power Input Port	DC48-57V, 5 Pin industrial Phoenix terminal, support anti reverse protection
Power Supply	No, optional 48V/60W or 48V/120W industrial power supply
<b>Physical Parameter</b>	
Operation TEMP / Humidity	-40°C ~ +75°C, 5% ~ 90% RH Non condensing
Storage TEMP / Humidity	-40°C ~ +85°C, 5% ~ 95% RH Non condensing

Dimension (L*W*H)	119*100*30mm
Net /Gross Weight	< 0.35 kg / <0.5 kg
Installation	Desktop, 35mm DIN rail
<b>Certification</b>	
Lightning Protection	Lightning protection: 6KV 8/20us; Protection level: IP40 IEC61000 4-2 (ESD): ±8kV contact discharge, ±15kV air discharge IEC61000 4-3 (RS):10V/m(80~1000MHz) IEC61000 4-4 (EFT): power cable: ±4kV; data cable: ±2kV IEC61000 4-5 (Surge): power cable:CM±4kV/ DM±2kV; data cable: ±4kV IEC61000 4-6 (radio frequency transmission):10V(150kHz~80MHz) IEC61000 4-8 (power frequency magnetic field):100A/m;1000A/m ,1s to 3s IEC61000 4-9 (pulsed magnet field):1000A/m IEC61000 4-10 (damped oscillation):30A/m 1MHz IEC61000 4-12/18(Shockwave):CM 2.5kV, DM 1kV IEC61000 4-16 (common mode transmission):30V; 300V,1s FCC Part 15/CISPR22(EN55022): Class B IEC61000 6-2 (Common Industrial Standard)
Mechanical Properties	IEC60068 2-6 (anti vibration) IEC60068 2-27 (anti shock) IEC60068 2-32 (free fall)
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS
<b>Network Management Features</b>	
Interface	Port status display, Port traffic statistics Port duplex/negotiation rate configuration EEE Energy saving and green Ethernet function IEEE802.3x flow control configuration (Full duplex)
VLAN	Port based IEEE802.1Q VLAN configuration (4K)
Port Aggregation	Static aggregation
Loop Protection	Loop protection function
Multicast	IGMP Snooping v1/v2, Max 256 multicast groups
Port Mirroring	Bidirectional data mirroring based on port
QoS	Diff-Serv QoS, Priority Mark/Remark 8*Output queues of each port, 802.1p/DSCP priority mapping
Security	Broadcast storm control, Port isolation, Port speed limit
DHCP	DHCP Snooping
Management	Mobile APP operation and maintenance management NMS platform management (Local platform/Cloud platform) One key recovery, Cable Diagnose, Web Management (HTTPS)
System	Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Category 5 and above Ethernet cables TCP/IP, network adapter, and network operating systems (Such as Microsoft Windows, Linux or Mac OS X) are installed on each computer in the network with Category 5 and above Ethernet cables

### Dimensions

