

5MP Outdoor Dome Camera HYU-CC-CIDV24001



Key Features

- 1/2.8" SONY Starvis Back-illuminated CMOS sensor
- H.265+/H.265/H.264+/H.264 Compression Method
- 5X Motor Zoom Auto Focus Lens
- IR Distance 30m
- IP66 Outdoor Metal Case

Specifications

Model	HYU-CC-CIDV24001
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	5MP
Effective Pixels	2616 (H) x 1964 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Minimum Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focus Length	2.7 - 13.5mm
Focus Control	Auto
Lens Type	Motorized
Night Vision	
Infrared LED	42μ x 4PCS
Infrared Distance	30M
IR Status	Auto Control
IR Power On	Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Wireless	/
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2592*1944@20fp, 2560*1920@20fp
Main Stream 2	2560*1440@25fp
Main Stream 3	720*480@15fps, 720*480@30fps
Sub Stream 1	720*480@15fps, 720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Third Stream	352*288@15fps, 352*288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK(Flicker Control), Video Tampering

Starlight	/
Corridor Pattern	Supported
Defog Mode	Supported
ROI	Supported
BLC	Supported
HDR	/
WDR	Supported
Motion Detection	Supported
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Interface	
Audio	Optional
Alarm	/
SD Card Slot	Optional, Support Max 128GB
RS485	/
General	
Housing	Metal, IP66
Anti-cut Bracket	Optional
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 950mA
Dimension	φ142 x 142(H)mm
Weight	1200g