BLAUPUNKT

User Manual

RoHS COMPLIANT 1.25GBPS 1310/1550NM&1550/1310NM TRANSCEIVER 20KM BP-SFPBID-SM



Enjoy it.

FEATURES:

- Supports 1.25Gbps/1.0625Gbps bit rates
- Bi-Directional LC connector
- Hot pluggable SFP footprint
- T:1310nm FP laser and1550nm PIN photo detector
- R:1550nm DFB laser and 1310nm PIN photo detector
- Applicable for 20Km SMF connection
- Low power consumption, < 0.8W
- Digital Diagnostic Monitor Interface
- Very low EMI and excellent ESD protection
- Operating case temperature: Commercial: 0 to 70 °C

APPLICATIONS:

- Gigabit Ethernet
- Fiber Channel
- Switch to Switch interface
- Switched backplane applications
- Router / Server interface
- Other optical transmission systems

For Inquiries, Please contact:

Security Shop doo
Vladimira Nazora 1, 11077 Novi Beograd
Tel: +381 11 318 68 68
www.securityshop.rs

BLAUPUNKT and the BLAUPUNKT logo are trademarks of TALISMAN BRANDS (Luxembourg) S.A.R.L.and are used under license from Talisman Brands, Inc. BLAUPUNKT licensees are solely responsible for the BLAUPUNKT branded products manufactured, distributed and sold under license.
www.blaupunkt.com