

HYUNDAI

LOW PROFILE BASE

HYU-FD-8TRB001

USER MANUAL

Description

Low profile 102 mm diameter bases are used with 2-wire and 4-wire fire detection and alarm system detectors. The range includes a continuity feature that maintains the alarm zone circuit wiring continuity when a device is removed from the base.

The low-profile bases are suitable for installation on surfaces where the device connection cable can penetrate the mounting surface.

The range of bases provides fire detection and alarm system designers with Standards-compliant products that are easy to install and that provide a reliable connection to the connected device.

Features

- Secure mounting to all surfaces
- Cable entry points through the rear
- Alarm zone circuit continuity models available
- Plated contacts for durable connection to detectors
- Fitted square washer to easy and reliable cable clamping
- Terminals suitable for (0.4 ~ 2.5) mm² diameter wiring
- Low maintenance

Compliance

Bases are approved by conformance assessment agencies as part of the device compliance (see device datasheets).

The following bases have specific approvals.

	UL ^{a, b}	CE ^c
HYU-FD-4TRB001	✓	✓
HYU-FD-8TRB00	✓	✓

Specifications

	HYU-FD-4TRB001		HYU-FD-8TRB00	
Number of terminals	4		8	
Diameter	102 mm			
Height	16 mm			
Colour	White			



)

Ordering Information

Part number	2-wire	4-wire	Continuity
HYU-FD-4TRB001	✓	—	—
HYU-FD-8TRB00	✓	—	—

HYUNDAI

For Inquiries, Please Contact:

Security Shop
Vladimira Popovica 6/6/A606
11070 Novi Beograd, Serbia
Tell +381 11 318 68 68
office@securityshop.rs

Imported/Distributed by Security Shop Doo
Licensed by Hyundai Corporation Holdings, Korea
Delivery and After Service shall only be covered within Serbia