

CAMERA QUICK INSTALLATION GUIDE

USER MANUAL HYU-CC-CHBV12001

Camera Quick Installation Guide


Remind:

- Fix expansion rubber plugs to the wall first if it is concrete wall. Install it directly with screws if it is a wooden wall.
- The installation of all terminal equipment such as control, display, and recording of the camera should be smooth and easy to operate.
- All cables in the control room shall be provided with cable troughs and inlet holes according to the installation location of the equipment. They shall be arranged, bundled neatly, numbered, and permanently marked.
- The pictures in this manual are for reference only. Please refer to the actual product for the final product.

Small Waterproof Series



Fix the bracket to the wall with screws.



Adjust the viewing angle. Loosen the screws to adjust the angle (A for vertical angle, B for axial angle).




Tighten the screws with hex wrench to complete the installation.


Conch Series Quick Installation Guide

Large Waterproof Series

If you have an external card slot, loosen the two screws first, remove the card cover, attach the memory card, and finally lock the card cover.



Rear Mounting Bracket Installation





Fix the bracket to the wall with 4 screws


Adjust the viewing angle. Loosen the regulation screw to adjust the angle. Tighten the screws with hex wrench to complete the installation.

Camera Quick Installation Guide

Bottom Mounting Bracket Installation









Adjust the viewing angle. Loosen the screws at A/B to adjust the angle (A for horizontal angle, B for vertical angle). Tighten the screws to complete the installation.

Conch Series Quick Installation Guide




Screw the main body into the base to complete the installation.

Small Hemisphere Series Quick Installation Guide




chassis assembly with 3 screws.

Big Hemisphere Series Quick Installation Guide




The factory default is the best angle, if you need to adjust:

Loosen 4 screws and remove the cover. Rotate the movement horizontally and vertically to adjust the angle.




Remove the rubber plug Slide the main body into the and fix the base with 4 screws. notch into the base.




Lock the screws, fix the ball to complete the installation.

Big Hemisphere Series Quick Installation Guide




First remove the fast iron from the bracket body and fasten the fast iron to the wall with 4 screws. Remove the rubber plug from the outlet hole, insert the main body of the camera with the camera into the quick iron, and fix the 4 screws.

Microcomputer Series Quick Installation Guide



Loosen 2 screws to separate the bracket from the camera body.



Use 4 screws to lock the bracket to the top wall or lock it to the side wall.



Use 2 screws to lock the camera body and the bracket together.

Do not lock first, adjust the angle, tighten the screws to complete the installation.



For Inquiries, Please Contact:

SECURITY SHOP

Vladimira Popovića 6, 11070 Novi Beograd, Srbija TEL: 011 318 68 68, 066 320015 E MAIL: office@securityshop.rs

Imported/Distributed by Security Shop Doo Licensed by Hyundai Corporation Holdings, Korea Delivery and After Service shall only be covered within Serbia