

**Waterproof No Touch Button HYU-AC-AEBTNT001** 

USER MANUAL



User Manual


# Main Features

> IP66 waterproof
> Zinc-alloy housing
> Output contact: NO/NC/COM
> Sensor distance: 3~10cm (Adjustable)
> Red LED indicator: standby
> Green LED indicator: active
> 5s, 10s or Toggle Mode Timer Delay (Optional) Specifications

Operating Voltage Idle Current Working Current	10~24V DC ≤15mA ≤25mA	
Current Rating	2A	
Sensor Distance	3~10cm (Adjustable)	
Output	NC or NO	
Infrared Wavelength	940 nm	
Timer Delay (Optional)	5s / 10s / Toggle Mode	
Environment Operating Temperature Operating Humidity	IP66 Waterproof -20°C~+60°C 0%~95%	
Physical Dimension Unit Weight Shipping Weight	Zinc-alloy Diameter: 73mm, Thickness: 20mm (Round) L105 x W69 x H20 mm(Ellipse) 145(Round) 215(Ellipse) 230(Round) 305(Ellipse)	

Wire Color	Function	Notes
Red	Power+	10~24 Volts DC
Black	GND	Gound
Green	NC	Nomally Closed
Brown	COM	Common
White	NO	Normally Open

## Sensor Distance and Timer Delay (Optional) Adjustment



### Packing List

Item	Quantity
Gift Box	1
No Touch Button	1
Manual	1
Self Tapping Screw	2
Wall Fixing Plug	2

