HYUNDAI
SECURITY DEVICE

Addressable repeater panel
HYU-FA-AREP001

User Manual

GENUINE PRODUCT OF
HYUNDAI CORPORATION

HYUNDAI

addressable DC repeater panel

CE

Repeater panel for 2-wire addressable system applications

Description

The 6001 addressable DC repeater panel extends the 6001 addressable control and indicating equipment display to a remote location. The repeater panel is compatible with all Numens 6001 CIE and can be powered from the existing DC 24 V supply.

The repeater panel comes standard with features that allows flexibility and expandability. Default configuration programming facilitates out-of-box installation and rapid commissioning.

The 6001 DC repeater panel provides fire detection and alarm system designers with a premium product for life safety and property protection applications.

addressable DC repeater panel

Features

- Backlit LCD display provides 4 rows of 40 characters
- 16 separate fire alarm zone LED indicators
- Recessed mounting enclosure
- Powered from the control and indicating equipment DC 24 V supply
- Up to 64 repeater panels can be connected to a single control and indicating equipment
- Easy installation

Compliance

DC repeater panels have CE marking.

Note: There are no European standards for repeater panels.

Specifications

	HYU-FA-AREP001
Operating voltage	DC (21 ~ 28) V
Quiescent current	90 mA @ DC 28 V
Number of networkable repeater panels	64
Terminal wiring	(0.4 ~ 2.5) mm^2
Operating temperature	(-5 ~ +40) °C
Operating humidity	(0 ~ 95) % RH, non-condensing
Storage temperature	(-25 ~ +80) °C
Storage humidity	(0 ~ 98) % RH, non-condensing
Dimensions (h × w × d)	(180 × 260 × 73) mm
Weight (excluding batteries)	1.2 kg

HYUNDAI

GENUINE PRODUCT OF
HYUNDAI CORPORATION

For Inquiries, Please Contact:

Security Shop
Vladimira Nazora 1
11077 Novi Beograd, Serbia
Tel: +381 11 318 68 68
office@securityshop.rs

Imported/Distributed by Security Shop doo
Licensed by Hyundai Corporation Holdings, Korea
Delivery and After Service shall only be covered within Serbia